



| | | | |
|------|---------|-----|----------|
| REV | CONTENT | CHK | DATE |
| V0.1 | 修改公差 | CXL | 15.04.20 |

- NOTES:
1. Rating:300V 15A ;
 2. Insulation Withstands Voltage: AC2000V/MIN
 3. Insulation Resistance: 500MΩ or more at DC500V
 4. Using Temperature Range: -40°C~+105°C
 5. "★" is the important dimension

Kinghelm®

| Total Pitch Tolerances in mm | | | | | | | | | | Nominal dimension range in mm | | | | | | | | | | ⊥ | ≡ | - | // | | |
|------------------------------|---------|---------|---------|---------|----------|----------|----------|----------|----------|-------------------------------|---------|---------|---------|---------|----------|----------|----------|----------|----------|------|-------|-----|------|--------|--------|
| over 0 | over 30 | over 53 | over 70 | over 90 | over 115 | over 150 | over 250 | over 350 | over 500 | over 0 | over 30 | over 53 | over 70 | over 90 | over 115 | over 150 | over 200 | over 250 | over 320 | to 0 | to 10 | all | to 0 | to 100 | to 150 |
| ±0.18 | ±0.20 | ±0.25 | ±0.3 | ±0.35 | ±0.44 | ±0.60 | ±0.70 | ±0.85 | ±0.20 | ±0.25 | ±0.30 | ±0.35 | ±0.44 | ±0.55 | ±0.70 | ±0.80 | ±0.90 | 0.2 | 0.3 | 0.3 | 0.2 | 0.3 | 0.5 | | |

| | | | | | |
|-------------------|--------------|-------------|------------|---------------------|-------------|
| 2 | SOLDER.PIN | ZF300B0001 | P | BRASS | Tin Plated |
| 1 | HOUSING | ZF600A0XXXX | 1 | PA66 | UL94V-0 |
| ITEM | NAME OF PART | NO. OF PART | Q'TY | MATERIAL | NOTE |
| DWG. | SK | DATE | 2014/08/20 | SIZE A4 | UNITS mm |
| CHK. | | DATE | | SCALE 2.5:1 | 2EDG-7.62 |
| APP. | | DATE | | NAME | F600V-XXP-X |
| 深圳市金航标电子有限公司 | | | | www.kinghelm.com.cn | |
| KH-F600V-9P-7.62G | | | | 0755-28190160 | |