



1. Material:
 Contact: Phosphor Bronze
 Insulator: PBT+30% G.F. UL 94V-0
 Shell: SPCC
2. Mechanical:
 Mating: 35N max.
 Withdraw Force: 10N min.
 Durability: 1500 cycles min.
3. Electrical:
 Current-max (amps) 1.5A
 Voltage-max (volts) 30V
 Withstanding Voltage 750V AC
 Contact Resistance (ohms) 30 milliohms max insulation
 Resistance (ohms) 1000 Megohms min.
4. Plating:
 Contacts: Gold And Tin Over Nickel Plated
 Shell: Nickel over all plating.
5. Environmental:
 Temperature Range: -55 to 85

产品图 <small>MANUFACTURE PART</small>		公差一览表 <small>TOLERANCE UNLESS OTHERWISE SPECIFIED</small>		深圳市金航标电子有限公司 KH-2A90ZL-11.5		WWW.BDS666.COM 0755-83044319	
单位	公差	单位	公差	画法	制图	审核	
MM	±0.20	INCH	±	比例	设计	核准	
X	±0.10	XX	±	SCALE	DESIGN	APPRO	
.XXX	±0.05	XXX	±	原本	图号	DCCL	版本 1/
2013.08.29				AI			第 1/ 页