



编 号	尺寸 (mm)	
	A	B
A2015-2X02Y	2.00	6.00
A2015-2X03Y	4.00	8.00
A2015-2X04Y	6.00	10.00
A2015-2X05Y	8.00	12.00
A2015-2X06Y	10.00	14.00
A2015-2X07Y	12.00	16.00
A2015-2X08Y	14.00	18.00
A2015-2X09Y	16.00	20.00
A2015-2X10Y	18.00	22.00
A2015-2X11Y	20.00	24.00
A2015-2X12Y	22.00	26.00
A2015-2X20Y	38.00	42.00

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material:Houing Nylon66, UL94V-0

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENEERL TOLERANCE		制图 DRAWING	钱岳生 2013、11、01		料号 PART NO.	A2015-2XNY		版本 REV.	A
			X.±0.25	X.*±2'	审核 CHECK	张名 2013、11、03		品名 TITLE	SPH孔座		页次 SHEET	1/1
			.X±0.20	.X'±1'	核准 APPROVAL	张名 2013、11、05		客户料号 CUTM. NO.	深圳市金航标电子有限公司		www.kinghelm.com.cn	
			.XX±0.15	.XX'±0.5'	单位 UNITS	MM	比例 SCALE	1:1	KH-A2015-2X11Y		0755-28190160	
			.XXX±0.10	.XXX'±0.5'								